



US 20220393675A1

(19) **United States**

(12) **Patent Application Publication**  
**LI et al.**

(10) **Pub. No.: US 2022/0393675 A1**

(43) **Pub. Date: Dec. 8, 2022**

(54) **ACTIVELY TRACKING SWITCHING SPEED CONTROL AND REGULATING SWITCHING SPEED OF A POWER TRANSISTOR DURING TURN-ON**

(71) Applicant: **Infineon Technologies AG**, Neubiberg (DE)

(72) Inventors: **Zheming LI**, Bayreuth (DE);  
**Mark-Matthias BAKRAN**, Erlangen (DE); **Daniel DOMES**, Ruethen (DE);  
**Robert MAIER**, Bayreuth (DE);  
**Franz-Josef NIEDERNOSTHEIDE**, Hagen Am Teutoburger Wald (DE)

(73) Assignee: **Infineon Technologies AG**, Neubiberg (DE)

(21) Appl. No.: **17/852,785**

(22) Filed: **Jun. 29, 2022**

**Related U.S. Application Data**

(63) Continuation of application No. 17/372,913, filed on Jul. 12, 2021, now Pat. No. 11,444,613.

(60) Provisional application No. 63/197,566, filed on Jun. 7, 2021.

**Publication Classification**

(51) **Int. Cl.**

**H03K 17/04** (2006.01)

**H03K 17/042** (2006.01)

(52) **U.S. Cl.**

**CPC** ..... **H03K 17/0406** (2013.01); **H03K 17/042**

(2013.01); **H03K 17/04206** (2013.01); **H03K**

**2217/0027** (2013.01)

(57)

**ABSTRACT**

A gate driver system includes a gate driver circuit coupled to a gate terminal of a transistor and configured to generate an on-current during a plurality of turn-on switching events to turn on the transistor, wherein the gate driver circuit includes a first driver configured to source a first portion of the on-current to the gate terminal to charge a first portion of the gate voltage and a second driver configured to, during a first boost interval, source a second portion of the on-current to the gate terminal to charge a second portion of the gate voltage; a measurement circuit configured to measure a transistor parameter indicative of an oscillation of a load current for a turn-on switching event; and a controller configured to receive the measured transistor parameter and regulate a length of the first boost interval based on the measured transistor parameter.

