



(19) **United States**
(12) **Patent Application Publication**
HEO et al.

(10) Pub. No.: US 2024/0237479 A9
(48) Pub. Date: Jul. 11, 2024
CORRECTED PUBLICATION

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(72) Inventors: **Eui Kang HEO**, Yongin-si (KR);
Chong Sup CHANG, Yongin-si (KR)

(73) Assignee: **Samsung Display Co., LTD.**, Yongin-si
(KR)

(21) Appl. No.: 18/322,659

(22) Filed: **May 24, 2023**

Prior Publication Data

(15) Correction of US 2024/0138231 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(65) US 2024/0138231 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 21, 2022 (KR) 10-2022-0136617

Publication Classification

(51) **Int. Cl.**
H10K 59/80 (2006.01)
H10K 59/12 (2006.01)
H10K 59/124 (2006.01)
H10K 59/88 (2006.01)

(52) **U.S. Cl.**
 CPC ... *H10K 59/80522* (2023.02); *H10K 59/1201*
 (2023.02); *H10K 59/124* (2023.02); *H10K*
59/88 (2023.02)

(57) **ABSTRACT**

A display device includes a thin-film transistor, an interlayer insulating layer on the thin-film transistor, a source electrode, a drain electrode, and an auxiliary electrode on the interlayer insulating layer, each of the source electrode, the drain electrode, and the auxiliary electrode including a main conductive layer and a sub conductive layer on the main conductive layer, and a via insulating layer on the source electrode, the drain electrode and the auxiliary electrode, the via insulating layer covering the source electrode and the drain electrode and exposing a portion of an upper surface of the second conductive layer of the auxiliary electrode. The via insulating layer includes a first part spaced apart from the upper surface of the second conductive layer of the auxiliary electrode, and the second part adjacent to side surfaces of the main conductive layer and the sub conductive layer of the auxiliary electrode.

