

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2023/0231150 A1 Kim et al.

Jul. 20, 2023 (43) **Pub. Date:**

(54) STAINLESS STEEL FOR FUEL CELL **SEPARATOR**

(71) Applicant: POSCO, Pohang-si, Gyeongsangbuk-do (KR)

(72) Inventors: Kwangmin Kim, Pohang-si,

Gyeongsangbuk-do (KR); Yongho Kim, Pohang-si, Gyeongsangbuk-do (KR);

Bo-sung Seo, Pohang-si,

Gyeongsangbuk-do (KR); Dong-hoon Kim, Pohang-si, Gyeongsangbuk-do

(KR)

Assignee: POSCO, Pohang-si, Gyeongsangbuk-do

(KR)

(21) Appl. No.: 17/924,530

(22) PCT Filed: Oct. 16, 2020

(86) PCT No.: PCT/KR2020/014195

§ 371 (c)(1),

(2) Date: Nov. 10, 2022

(30)Foreign Application Priority Data

May 29, 2020 (KR) 10-2020-0065190

Publication Classification

51)	Int. Cl.	
	H01M 8/021	(2006.01)
	C25D 11/34	(2006.01)
	C22C 38/50	(2006.01)
	C22C 38/48	(2006.01)
	C22C 38/46	(2006.01)
	C22C 38/44	(2006.01)
	C22C 38/34	(2006.01)
	C22C 38/04	(2006.01)
	C22C 38/02	(2006.01)
	C22C 38/00	(2006.01)

(52)U.S. Cl.

> (2013.01); C22C 38/50 (2013.01); C22C 38/48 (2013.01); C22C 38/46 (2013.01); C22C 38/44 (2013.01); C22C 38/34 (2013.01); C22C 38/04 (2013.01); C22C 38/02 (2013.01); C22C 38/001 (2013.01); C22C 38/004 (2013.01)

(57)ABSTRACT

Disclosed is a stainless steel for a fuel cell separator, more specifically, a stainless steel for a fuel cell separator having a low contact resistance. According to an embodiment of the stainless steel for a fuel cell separator disclosed herein, an arithmetic mean summit curvature Ssc of the surface defined according to the ISO 25178 standard is at least 6.0 μm^{-1} , a root mean square surface slope Sdq is at least 23, and a contact resistance is at most $10 \text{ m}\Omega \cdot \text{cm}^2$.

CONTACT RESISTANCE

$(m\Omega\cdot cm^2)$

