US 20240214401A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0214401 A1

KAMIGUCHI (43) Pub. Date: Jun. 27, 2024

(54) **IN-VEHICLE RELAY DEVICE, RELAY METHOD, AND RELAY PROGRAM**

(71) Applicants: **AutoNetworks Technologies, Ltd.**, Yokkaichi-shi, Mie (JP); **Sumitomo Wiring Systems, Ltd.**, Yokkaichi-shi, Mie (JP); **Sumitomo Electric Industries, Ltd.**, Osaka-shi, Osaka (JP)

(72) Inventor: **Shogo KAMIGUCHI**, Yokkaichi-shi, Mie (JP)

(21) Appl. No.: **18/557,378**

(22) PCT Filed: **Mar. 25, 2022**

(86) PCT No.: **PCT/JP2022/014247**

§ 371 (c)(1),
(2) Date: **Oct. 26, 2023**

(30) **Foreign Application Priority Data**

Apr. 28, 2021 (JP) 2021-076437

Publication Classification

(51) **Int. Cl.**

H04L 9/40	(2006.01)
B60R 16/023	(2006.01)
H04L 12/44	(2006.01)

(52) **U.S. Cl.**

CPC ***H04L 63/1416*** (2013.01); ***B60R 16/0231*** (2013.01); ***H04L 12/44*** (2013.01)

(57) **ABSTRACT**

Provided is an in-vehicle relay device including a relay unit that relays frames transmitted and received between one in-vehicle device and another in-vehicle device in an in-vehicle network, a calculation unit that calculates a processing load of the other in-vehicle device based on frames that were received from the in-vehicle device by the relay unit and are addressed to the other in-vehicle device, and a determination unit that determines whether or not the relay unit is to relay the frames addressed to the other in-vehicle device based on the processing load calculated by the calculation unit.

In-vehicle ECU	Processing target frames	Load increase rate	Processing time	Threshold
A	No.1	a %	w ms	M %
	No.2	b %	x ms	
B	No.1	c %	y ms	N %
	No.3	d %	z ms	