



US 20240215293A1

(19) **United States**

(12) **Patent Application Publication**

MANAGAKI

(10) **Pub. No.: US 2024/0215293 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventor: **Nobuto MANAGAKI**, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(21) Appl. No.: **18/391,719**

(22) Filed: **Dec. 21, 2023**

(30) **Foreign Application Priority Data**

Dec. 23, 2022 (JP) ..... 2022-206958

**Publication Classification**

(51) **Int. Cl.**  
*H10K 50/15* (2006.01)  
*H10K 59/35* (2006.01)  
*H10K 71/10* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *H10K 50/156* (2023.02); *H10K 59/35* (2023.02); *H10K 71/10* (2023.02)

(57) **ABSTRACT**

According to one embodiment, a display device includes a first anode, a cathode opposing the first anode and a first organic layer located between the first anode and the cathode, and the first organic layer includes a first light emitting layer and a hole transport layer located between the first anode and the first light emitting layer, and an average particle diameter per unit area of a material which constitutes the first light emitting layer is smaller than an average particle diameter per unit area of a material which constitutes the hole transport layer.

