

(19) United States

(12) Patent Application Publication CHO et al.

(54) BATTERY CHARGER INTEGRATED CIRCUIT FOR ADAPTIVELY LIMITING OVER-CURRENT, MOBILE DEVICE COMPRISING THE SAME AND OPERATION METHOD THEREOF

(71) Applicant: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR)

Inventors: Daewoong CHO, Suwon-si (KR); Kyeseok YOON, Suwon-si (KR); Seunghoon KIM, Suwon-si (KR); Jeongdu YOO, Suwon-si (KR); Sungwoo LEE, Suwon-si (KR); Jungwook HEO, Suwon-si (KR)

(73) Assignee: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR)

Appl. No.: 18/199,732

(22) Filed: May 19, 2023

Prior Publication Data

Correction of US 2024/0136833 A1 Apr. 25, 2024 (15)See (22) Filed. See (30) Foreign Application Priority Data.

(65) US 2024/0136833 A1 Apr. 25, 2024

Jul. 11, 2024 (48) **Pub. Date:** CORRECTED PUBLICATION

(10) Pub. No.: US 2024/0235221 A9

(30)Foreign Application Priority Data

Oct. 25, 2022 (KR) 10-2022-0138102

Publication Classification

(51) Int. Cl. H02J 7/00 (2006.01)

U.S. Cl. CPC H02J 7/00304 (2020.01); H02J 7/00714 (2020.01); **H02J** 7/**007182** (2020.01)

(57)ABSTRACT

A circuit includes: an overcurrent limiting (OCL) detector configured to detect whether a level of an inductor current reaches an OCL level and to generate an OCL detection voltage; a control loop circuit configured to generate a reset voltage by comparing a ramp voltage reflecting the level of the inductor current with an error voltage generated based on an operating condition that is out of a preset operating condition; an adaptive OCL controller configured to generate an OCL control current by counting a number of pulses of the OCL detection voltage and a number of pulses of the reset voltage; an oscillator configured to generate an oscillation voltage wherein a frequency of the oscillation voltage varies based on a magnitude of the overcurrent limit control current; and a switching transistor for switching the inductor current based on the oscillation voltage.

