



US 20230231827A1

(19) **United States**(12) **Patent Application Publication****Tang et al.**(10) **Pub. No.: US 2023/0231827 A1**(43) **Pub. Date:****Jul. 20, 2023**(54) **PER-NAMESPACE IP ADDRESS
MANAGEMENT METHOD FOR CONTAINER
NETWORKS**(71) Applicant: **VMware, Inc.**, Palo Alto, CA (US)(72) Inventors: **Qiang Tang**, Beijing (CN); **Zhaoqian
Xiao**, Beijing (CN)(21) Appl. No.: **17/684,169**(22) Filed: **Mar. 1, 2022**(30) **Foreign Application Priority Data**

Jan. 14, 2022	(WO)	PCTCN2022071987
Jan. 14, 2022	(WO)	PCTCN2022071988

Publication Classification(51) **Int. Cl.****H04L 61/5061** (2006.01)**H04L 61/2592** (2006.01)**H04L 12/46** (2006.01)(52) **U.S. Cl.**CPC **H04L 61/2061** (2013.01); **H04L 61/2592**
(2013.01); **H04L 12/4633** (2013.01)

(57)

ABSTRACT

Some embodiments of the invention provide a method of sending data in a network that includes at least one worker node executing one or more sets of containers and a virtual switch, the virtual switch including a gateway interface, a virtual local area network (VLAN) tunnel interface, and a set of virtual Ethernet interfaces associated with the one or more sets of containers. The method configures the gateway interface of the worker node to associate the gateway interface with multiple subnets that are each associated with a namespace. The worker node executes at least (1) first and second sets of containers of a first namespace, and (2) a third set of containers of a second namespace. The method sends data between the first and second sets of containers through a first virtual Ethernet interface associated with the first set of containers and a second virtual Ethernet interface associated with the second set of containers. The method sends data between the first set of containers and the third set of containers through the first virtual Ethernet interface associated with the first set of containers, the gateway interface, and a third virtual Ethernet interface associated with the third set of containers.

