

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0179832 A1 Geng et al. (43) Pub. Date:

(54) MULTI-ENTRY SOCKET POWER DELIVERY STRUCTURE AND BACKPLATE

(71) Applicants: Phil Geng, Washougal, WA (US); Xiaoning Ye, Portland, OR (US); Yipeng Zhong, Shanghai (CN); Meng Wang, Shanghai (CN); Hongfei Yan, Mesa, AZ (US); Chuansheng Liu, Shanghai (CN); Lejie Liu, Portland, OR (US); Mohanraj Prabhugoud, Portland, OR (US); Fernando Gonzalez Lenero, Zapopan (MX); Dongwang Chen, Shanghai (CN); Sanjoy Saha, Portland, OR (US); Ralph Miele, Hillsboro, OR (US); Baris Bicen, Chandler, AZ (US); David Shia, Portland, OR (US); Jefforv Smalley, Olympia, WA (US); Eric Erike, Mesa, AZ (US)

(72) Inventors: **Phil Geng**, Washougal, WA (US); Xiaoning Ye, Portland, OR (US); Yipeng Zhong, Shanghai (CN); Meng Wang, Shanghai (CN); Hongfei Yan, Mesa, AZ (US); Chuansheng Liu, Shanghai (CN); Lejie Liu, Portland, OR (US); Mohanraj Prabhugoud, Portland, OR (US); Fernando Gonzalez Lenero, Zapopan (MX); Dongwang Chen, Shanghai (CN); Sanjoy Saha, Portland, OR (US); Ralph Miele, Hillsboro, OR (US); Baris Bicen, Chandler, AZ (US); David Shia, Portland, OR (US); Jeffory Smalley, Olympia, WA (US); Eric Erike, Mesa, AZ (US)

Appl. No.: 18/435,821

(22)Filed: Feb. 7, 2024

(30)Foreign Application Priority Data

Jan. 25, 2024 (WO) PCT/CN2024/074050

May 30, 2024

Publication Classification

(51) Int. Cl. H05K 1/02 (2006.01)

(52) U.S. Cl. H05K 1/0263 (2013.01); H05K 2201/10189 (2013.01); H05K 2201/2009 (2013.01)

(57)**ABSTRACT**

A multi-entry socket power delivery structure is attachable to a printed circuit board to provide improved delivery of one or more power supply signals to a socket. The power delivery structure provides an additional path for power supply signals to be delivered to a socket (in addition to the "power corridor" of the printed circuit board). The power delivery structure comprises one or more portions, with individual portions comprising a printed circuit board connection portion that attaches to the printed circuit board to receive a power supply signal generated by a voltage regulator, and a socket connection portion that attaches to the printed circuit board to deliver the power supply signal to the socket via the printed circuit board. The power delivery structure can be located in the recess of a reinforced backplate that provides structural integrity to a processor stack and associated thermal management solution loading mechanism.

