

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0214119 A1 JANG et al.

Jun. 27, 2024 (43) **Pub. Date:**

(54) PUNCTURING-BASED 240 MHZ TRANSMISSION

(71) Applicant: LG ELECTRONICS INC., Seoul

(KR)

(72) Inventors: Insun JANG, Seoul (KR); Jeongki

KIM, Seoul (KR); Jinsoo CHOI, Seoul (KR); Eunsung PARK, Seoul (KR)

(73) Assignee: LG ELECTRONICS INC., Seoul

(KR)

(21) Appl. No.: 18/594,629

(22) Filed: Mar. 4, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/211,449, filed on Jun. 19, 2023, now Pat. No. 11,956,080, which is a continuation of application No. 17/775,238, filed on Sep. 7, 2022, filed as application No. PCT/KR2020/ 015628 on Nov. 9, 2020.

(30)Foreign Application Priority Data

Nov. 7, 2019	(KR)	10-2019-0142124
Dec. 5, 2019	(KR)	10-2019-0161031
Jun. 16, 2020	(KR)	10-2020-0073144
Jun. 19, 2020	(KR)	10-2020-0075163

Publication Classification

(51) Int. Cl. H04L 1/00 (2006.01)

(52) U.S. Cl. CPC *H04L 1/0069* (2013.01)

(57)ABSTRACT

In a wireless local area network (WLAN) system, a transmission STA can transmit a PPDU via a 320 MHz channel, and a Medium Access Control (MAC) signal may be generated for the PPDU. The MAC signal may include puncturing pattern information and channel center frequency segment (CCFS) information for a 320 MHz band. The CCFS information may include a first CCFS field related to channel center frequency (CCF) information of a primary 160 MHz channel, and a second CCFS field related to CCF information of a 320 MHz channel.



