US 20230232351A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0232351 A1**

KO et al. (43) **Pub. Date: Jul. 20, 2023**

(54) **METHOD AND APPARATUS FOR SELECTING PLURALITY OF TIME SYNCHRONIZATIONS IN NR V2X**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventors: **Woosuk KO**, Seoul (KR); **Hanbyul SEO**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(21) Appl. No.: **18/007,728**

(22) PCT Filed: **Jun. 3, 2021**

(86) PCT No.: **PCT/KR2021/006954**

§ 371 (c)(1),
(2) Date: **Dec. 1, 2022**

Related U.S. Application Data

(60) Provisional application No. 63/034,378, filed on Jun. 3, 2020, provisional application No. 63/034,955, filed on Jun. 4, 2020.

(30) **Foreign Application Priority Data**

Jun. 17, 2020 (KR) 10-2020-0073483

Publication Classification

(51) **Int. Cl.**

H04W 56/00	(2006.01)
H04W 72/25	(2006.01)
H04W 72/542	(2006.01)

(52) **U.S. Cl.**

CPC ***H04W 56/0015*** (2013.01); ***H04W 56/002*** (2013.01); ***H04W 72/25*** (2023.01); ***H04W 72/542*** (2023.01); *H04W 4/40* (2018.02)

(57) **ABSTRACT**

A method by which a first apparatus performs wireless communication is proposed. The method may comprise the steps of: selecting a first synchronization source, on the basis of a sidelink synchronization priority; obtaining a first synchronization, on the basis of the first synchronization source; receiving a plurality of synchronization signals from a plurality of synchronization sources; obtaining a plurality of synchronizations, on the basis of the plurality of synchronization signals; selecting a second synchronization source from among the plurality of synchronization sources, on the basis of a gap between a time related to the first synchronization and a time related to a second synchronization being greater than or equal to a threshold value, wherein the second synchronization is obtained on the basis of the second synchronization source; and transmitting, to a second apparatus, a sidelink-synchronization signal block (S-SSB), on the basis of the first synchronization or the second synchronization. For example, the first synchronization source and the second synchronization source may comprise at least one of a global navigation satellite system (GNSS), a base station, or user equipment. For example, the S-SSB may comprise a sidelink primary synchronization signal (S-PSS), a sidelink secondary synchronization signal (S-SSS), and a physical sidelink broadcast channel (PSBCH).