



US 20240251670A1

(19) **United States**

(12) **Patent Application Publication**  
**KAKIZOE**

(10) **Pub. No.: US 2024/0251670 A1**

(43) **Pub. Date: Jul. 25, 2024**

(54) **ORGANIC LIGHT-EMITTING DEVICE AND  
METHOD FOR MAKING SAME**

**Publication Classification**

(71) Applicant: **KYULUX, INC.**, Fukuoka-shi, Fukuoka  
(JP)

(51) **Int. Cl.**

**H10K 85/60** (2006.01)

**H10K 50/12** (2006.01)

**H10K 101/20** (2006.01)

(72) Inventor: **Hayato KAKIZOE**, Fukuoka-shi,  
Fukuoka (JP)

(52) **U.S. Cl.**

CPC ..... **H10K 85/654** (2023.02); **H10K 85/626**  
(2023.02); **H10K 85/6572** (2023.02); **H10K**  
**85/658** (2023.02); **H10K 50/12** (2023.02);  
**H10K 2101/20** (2023.02)

(21) Appl. No.: **18/557,103**

(22) PCT Filed: **Mar. 30, 2022**

(86) PCT No.: **PCT/JP2022/015884**

§ 371 (c)(1),

(2) Date: **Oct. 25, 2023**

(30) **Foreign Application Priority Data**

Apr. 26, 2021 (JP) ..... 2021-073740

(57)

**ABSTRACT**

An organic light emitting device having a light emitting layer that contains a first organic compound (1) and a second organic compound (2) of a delayed fluorescent material, and a barrier layer containing a triplet-regulating compound (Q) in contact with the light emitting layer, and satisfying the following formulae has a long emission lifetime and is stable.  $E_{S1}$  represents a lowest excited singlet energy, and  $E_{T1}$  represents a lowest excited triplet energy.  $E_{S1}(1) > E_{S1}(Q) > E_{S1}(2)$   $E_{T1}(1) > E_{T1}(2) > E_{T1}(Q)$

