



US 20240213440A1

(19) **United States**(12) **Patent Application Publication**
SAKAI(10) **Pub. No.: US 2024/0213440 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **ELECTRODE BODY FOR NON-AQUEOUS RECHARGEABLE BATTERY, NON-AQUEOUS RECHARGEABLE BATTERY, AND METHOD FOR MANUFACTURING ELECTRODE BODY OF NON-AQUEOUS RECHARGEABLE BATTERY**(71) Applicants: **PRIMEARTH EV ENERGY CO., LTD.**, Kosai-shi, Shizuoka (JP);
TOYOTA JIDOSHA KABUSHIKI KAISHA, Toyota-shi, Aichi-ken (JP);
PRIME PLANET ENERGY & SOLUTIONS, INC., Tokyo (JP)(72) Inventor: **Ryotaro SAKAI**, Toyohashi-shi (JP)(73) Assignees: **PRIMEARTH EV ENERGY CO., LTD.**, Kosai-shi, Shizuoka (JP);
TOYOTA JIDOSHA KABUSHIKI KAISHA, Toyota-shi, Aichi-ken (JP);
PRIME PLANET ENERGY & SOLUTIONS, INC., Tokyo (JP)(21) Appl. No.: **18/545,659**(22) Filed: **Dec. 19, 2023**(30) **Foreign Application Priority Data**

Dec. 22, 2022 (JP) 2022-205405

Publication Classification(51) **Int. Cl.****H01M 4/131** (2010.01)**H01M 4/139** (2010.01)**H01M 4/62** (2006.01)**H01M 4/02** (2006.01)**H01M 10/0525** (2010.01)(52) **U.S. Cl.**CPC **H01M 4/131** (2013.01); **H01M 4/139** (2013.01); **H01M 4/625** (2013.01); **H01M 2004/021** (2013.01); **H01M 10/0525** (2013.01)(57) **ABSTRACT**

An electrode body for a non-aqueous rechargeable battery includes a positive electrode substrate and a positive electrode mixture layer. A ratio of a specific surface area of the positive electrode plate to a density of the positive electrode mixture layer is 1.0 to 2.0, inclusive. A ratio of a spring constant of the electrode body to the specific surface area of the positive electrode plate is 30 to 80, inclusive.

