



US 20240213425A1

(19) United States

(12) Patent Application Publication

Wang et al.

(10) Pub. No.: US 2024/0213425 A1

(43) Pub. Date: Jun. 27, 2024

(54) DISPLAY SUBSTRATE AND DISPLAY DEVICE

Publication Classification

(71) Applicants: CHENGDU BOE OPTOELECTRONICS TECHNOLOGY CO., LTD., Chengdu (CN); BOE TECHNOLOGY GROUP CO., LTD., Beijing (CN)

(72) Inventors: Rong Wang, Beijing (CN); Bo Zhang, Beijing (CN); Qian Ma, Beijing (CN); Xiangdan Dong, Beijing (CN); Xiaoqing Shu, Beijing (CN); Yagui Gao, Beijing (CN); Erlong Song, Beijing (CN); Jiaxing Zhao, Beijing (CN); Yuting Fu, Beijing (CN); Chengchu Tseng, Beijing (CN)

(51) Int. Cl.
H01L 33/62 (2006.01)
G09G 3/32 (2006.01)
H01L 25/16 (2006.01)
H01L 27/15 (2006.01)

(52) U.S. Cl.
CPC H01L 33/62 (2013.01); G09G 3/32 (2013.01); H01L 25/167 (2013.01); H01L 27/156 (2013.01); G09G 2310/0267 (2013.01)

(21) Appl. No.: 17/906,061

(22) PCT Filed: Oct. 22, 2021

(86) PCT No.: PCT/CN2021/125558

§ 371 (c)(1),
(2) Date: Sep. 9, 2022

(30) Foreign Application Priority Data

Apr. 15, 2021 (CN) 202110427389.8

(57) ABSTRACT

A display substrate and a display device are provided. The display substrate includes a plurality of pads, an insulating layer and an inorganic layer located in a peripheral region. At least one of the pads includes a first conductor portion, a second conductor portion and a third conductor portion. The third conductor portion is located on a side of the second conductor portion away from a base substrate and electrically connected to the second conductor portion. The third conductor portion is electrically connected to the second conductor portion through a second via hole disposed in the inorganic layer of the peripheral region. A projection of the first conductor portion on the base substrate is located within a projection of the second via hole on the base substrate.

