

# (19) United States

## (12) Patent Application Publication (10) Pub. No.: US 2022/0369471 A1 NIKOLIC et al.

## Nov. 17, 2022 (43) **Pub. Date:**

### (54) PRINTABLE ELECTRICAL COMPONENT COMPRISING A PLASTIC SUBSTRATE

(71) Applicant: FRESENIUS MEDICAL CARE **DEUTSCHLAND GMBH, Bad** 

Homburg, DE (US)

(72) Inventors: **Dejan NIKOLIC**, Bad Soden (DE);

Alexander HEIDE, Eppstein (DE); Daniel JURIC, Stuttgart (DE); Andre BUELAU, Stuttgart (DE); Juergen KECK, Filderstadt (DE); Jonathan SEYBOLD, Blaufelden (DE);

Karl-Peter FRITZ, Schonaich (DE); Kerstin GLAESER, Boeblingen (DE)

(73) Assignee: FRESENIUS MEDICAL CARE

**DEUTSCHLAND GMBH, Bad** 

Homburg (DE)

(21) Appl. No.: 17/766,536

PCT Filed: Oct. 9, 2020

(86) PCT No.: PCT/EP2020/078352

§ 371 (c)(1),

Apr. 5, 2022 (2) Date:

#### (30)Foreign Application Priority Data

(DE) ...... 10 2019 215 595.2

### **Publication Classification**

(51) Int. Cl. H05K 3/12 (2006.01)H05K 1/16 (2006.01)H05K 1/09 (2006.01)



(52) U.S. Cl.

CPC ...... H05K 3/125 (2013.01); H05K 1/16 (2013.01); H05K 1/092 (2013.01); H05K 2201/10151 (2013.01); H05K 2201/09263 (2013.01); H05K 2203/1131 (2013.01)

#### **ABSTRACT** (57)

The invention relates to a medical device comprising a printable electrical component (1), the printable electrical component (1) comprising a plastic substrate (L1) wherein at least electrical component (E) is applied to the plastic substrate, wherein the electrical component (E) comprises a dried conductive ink, wherein the plastic substrate is selected from the group comprising polycarbonate, cycloolefin copolymers, polymethylacrylate, polypropylene and wherein the dried conductive ink comprise silver and/or gold, wherein the electrical component (E) comprises feather-like and/or meander-like and/or spiral-shaped sections, whereby the medical device further comprises a fluid line, wherein the printable electrical component is located on the outside of the fluid line. The invention also relates to a medical device comprising a printable electrical component (1) the printable electrical component (1) comprising a plastic substrate (L1), wherein at least one electrical component (E) is applied to the plastic substrate, wherein the electrical component (E) comprises a dried conductive ink, wherein the plastic substrate is selected from a group comprising polycarbonate, cycloolefin copolymers, polymethyl-methacrylate, polypropylene and wherein the dried, conductive ink comprises silver and/or gold, wherein the electrical component (E) comprises at least one conductor section or at least two electrodes, characterized in that the electrical component (E) is part of an expansion sensor and/or a pressure sensor and/or a thermal flow sensor.

