



US 20240213901A1

(19) **United States**

(12) **Patent Application Publication**
Chen et al.

(10) **Pub. No.: US 2024/0213901 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **METHOD FOR CONTROLLING
MULTI-MOVER DIRECT DRIVE
TRANSMISSION SYSTEM AND RELATED
DEVICE**

Publication Classification

(51) **Int. Cl.**
H02P 25/06 (2006.01)
B65G 43/10 (2006.01)
H02P 23/12 (2006.01)
H02P 23/14 (2006.01)
(52) **U.S. Cl.**
CPC *H02P 25/06* (2013.01); *B65G 43/10*
(2013.01); *H02P 23/12* (2013.01); *H02P 23/14*
(2013.01)

(71) Applicant: **AAC Microtech (Changzhou) Co.,
Ltd.**, Changzhou City, Jiangsu Province
(CN)

(72) Inventors: **Min Chen**, Shenzhen (CN); **Xueyuan
Zhu**, Shenzhen (CN); **Shun Guo**,
Shenzhen (CN); **Lin Qian**, Shenzhen
(CN); **Weiling Shi**, Shenzhen (CN);
Wanlun Wang, Shenzhen (CN)

(21) Appl. No.: **17/918,549**

(22) PCT Filed: **Jul. 28, 2022**

(86) PCT No.: **PCT/CN2022/108444**

§ 371 (c)(1),

(2) Date: **Oct. 12, 2022**

(30) **Foreign Application Priority Data**

Jun. 30, 2022 (CN) 202210777097.1

(57) **ABSTRACT**

A method for controlling a multi-mover direct drive transmission system and related devices, including: S1: detecting a real-time position of the mover units movable in the feedback segments; S2: determining whether the mover unit enters junction region between the feedback and transition segments: if yes, calculating, by using preset algorithm, an electrical angle at which the mover unit moves in the transition segment, and determining real-time position of the mover unit through the electrical angle; and setting cooperative control mode of the stator windings in a range of the transition segment according to the real-time position of the mover unit; and S3: determining whether the mover unit enters the junction region between the transition segment and the feedback segment: if yes, feeding back real-time position of the mover unit through the displacement sensor of the feedback segment. The above solution has a good control effect, low costs, and low mounting requirements.

100
~

