

US 20240237416A9

(19) United States

(12) Patent Application Publication TABATAKE

(10) Pub. No.: US 2024/0237416 A9

(48) **Pub. Date: Jul. 11, 2024 CORRECTED PUBLICATION**

(54) **DISPLAY DEVICE**

(71) Applicant: Japan Display Inc., Tokyo (JP)

(72) Inventor: Hiroshi TABATAKE, Tokyo (JP)

(73) Assignee: Japan Display Inc., Tokyo (JP)

(21) Appl. No.: 18/399,954

(22) Filed: Dec. 29, 2023

Prior Publication Data

- (15) Correction of US 2024/0138197 A1 Apr. 25, 2024 See (30) Foreign Application Priority Data.
- (65) US 2024/0138197 A1 Apr. 25, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/185,549, filed on Mar. 17, 2023, now Pat. No. 11,903,264.

(30) Foreign Application Priority Data

Publication Classification

(51) Int. Cl. H10K 59/122 (2006.01) G09G 3/3225 (2006.01) H10K 59/131 (2006.01) H10K 59/80 (2006.01)

(52) U.S. Cl.

CPC *H10K 59/122* (2023.02); *G09G 3/3225* (2013.01); *H10K 59/131* (2023.02); *H10K 59/873* (2023.02); *G09G 2300/0452* (2013.01); *G09G 2300/0842* (2013.01)

(57) ABSTRACT

According to one embodiment, a display device includes a substrate, a circuit layer including a metal-made feed line in a surrounding area, an insulating layer covering the circuit layer, a lower electrode, a rib, a partition above the rib, an upper electrode connected to the partition, an organic layer between the electrodes and a conductive layer connected to the partition. The partition and the conductive layer each includes a metal-made lower portion and an upper portion protruding from a side surface of the lower portion. The lower portion of the conductive layer and the feed line are in contact with each other in the first contact portion in the surrounding area.

