US 20240251585A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0251585 A1**

MASUDA et al. (43) **Pub. Date: Jul. 25, 2024**

(54) **ORGANIC ELECTROLUMINESCENT ELEMENT, ORGANIC ELECTROLUMINESCENT DISPLAY APPARATUS, AND ELECTRONIC DEVICE**

(71) Applicant: **IDEMITSU KOSAN CO.,LTD.**, Tokyo (JP)

(72) Inventors: **Tetsuya MASUDA**, Tokyo (JP); **Satomi TASAKI**, Tokyo (JP); **Hiroaki TOYOSHIMA**, Tokyo (JP); **Masato NAKAMURA**, Tokyo (JP); **Kazuki NISHIMURA**, Tokyo (JP); **Hiroaki ITOI**, Tokyo (JP); **Emiko KAMBE**, Tokyo (JP)

(73) Assignee: **IDEMITSU KOSAN CO.,LTD.**, Tokyo (JP)

(21) Appl. No.: **18/288,147**

(22) PCT Filed: **Apr. 26, 2022**

(86) PCT No.: **PCT/JP2022/018803**

§ 371 (c)(1),
(2) Date: **Feb. 26, 2024**

(30) **Foreign Application Priority Data**

Apr. 26, 2021 (JP) 2021-074498

Publication Classification

(51) **Int. Cl.**

H10K 50/13	(2006.01)
H10K 50/15	(2006.01)
H10K 59/35	(2006.01)
H10K 101/60	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 50/131*** (2023.02); ***H10K 50/156*** (2023.02); ***H10K 59/35*** (2023.02); *H10K 2101/60* (2023.02)

(57) **ABSTRACT**

An organic EL device includes: an anode; a cathode; an emitting region; and a hole transporting zone, in which the emitting region includes a first emitting layer containing a first host material and a second emitting layer containing a second host material, at least one organic layer in the hole transporting zone is a first organic layer, the first organic layer contains a hole transporting zone material, the first emitting layer is disposed close to the anode, and a triplet energy of the first host material $T_1(H1)$ and a triplet energy of the second host material $T_1(H2)$ satisfy Numerical Formula 1, and a dipole of the first host material is 0.4 D or more,

$$T_1(H1) > T_1(H2) \quad \text{(Numerical Formula 1).}$$