US 20240214476A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0214476 A1**

Lochmann et al. (43) **Pub. Date: Jun. 27, 2024**

(54) **BUILDING TECHNOLOGY DEVICE**

(71) Applicant: **Tridonic GmbH & Co KG**, Dornbirn (AT)

(72) Inventors: **Frank Lochmann**, Achberg (DE); **Lukas Simma**, Hohenweiler (AT)

(73) Assignee: **Tridonic GmbH & Co KG**, Dornbirn (AT)

(21) Appl. No.: **17/909,800**

(22) PCT Filed: **Feb. 22, 2021**

(86) PCT No.: **PCT/EP2021/054348**

§ 371 (c)(1),
(2) Date: **Sep. 7, 2022**

(30) **Foreign Application Priority Data**

Mar. 11, 2020 (EP) 20162479.8

Publication Classification

(51) **Int. Cl.**
H04L 69/18 (2006.01)
H05B 45/30 (2006.01)
H05B 47/18 (2006.01)
H05B 47/19 (2006.01)

(52) **U.S. Cl.**
CPC ***H04L 69/18*** (2013.01); ***H05B 45/30*** (2020.01); ***H05B 47/183*** (2024.01); ***H05B 47/19*** (2020.01)

(57) **ABSTRACT**

The invention relates to a building technology device (**100**), for example an LED driver (**200**), comprising: a first control unit (**101**) and a second control unit (**103**), wherein the first control unit (**101**) is configured to execute a software, and wherein the second control unit (**103**) is configured to execute a further software, in particular an embedded software of the building technology device (**100**); an interface unit (**105**) arranged between the first control unit (**101**) and the second control unit (**103**); wherein the interface unit (**105**) comprises at least one external interface (**107**, **113**) which is connectable to an external device (**301**); and wherein the at least one external interface (**107**, **113**) is adapted to facilitate a selective communication between the external device (**301**) and the first control unit (**101**) and independently between the external device (**301**) and the second control unit (**103**).