



US 20220407490A1

(19) **United States**(12) **Patent Application Publication**
Park et al.(10) **Pub. No.: US 2022/0407490 A1**(43) **Pub. Date: Dec. 22, 2022**(54) **WIDEBAND SIGNAL ATTENUATOR****H03G 1/00** (2006.01)**H03G 3/30** (2006.01)(71) Applicant: **MEDIATEK Singapore Pte. Ltd.,**
Singapore (SG)(52) **U.S. Cl.**CPC **H03H 7/24** (2013.01); **H03H 11/245**
(2013.01); **H03G 1/007** (2013.01); **H03G 3/30**
(2013.01)(72) Inventors: **Henry Arnold Park**, San Jose, CA
(US); **Tamer Mohammed Ali**, San
Jose, CA (US)(73) Assignee: **MEDIATEK Singapore Pte. Ltd.,**
Singapore (SG)

(57)

ABSTRACT(21) Appl. No.: **17/744,163**(22) Filed: **May 13, 2022****Related U.S. Application Data**(60) Provisional application No. 63/213,305, filed on Jun.
22, 2021.**Publication Classification**(51) **Int. Cl.****H03H 7/24** (2006.01)**H03H 11/24** (2006.01)

Disclosed herein are embodiments of a wide bandwidth attenuator circuit having a tunable gain and tunable input impedance. In some embodiments, the wideband attenuator circuit comprises a serial capacitor shunted to ground by a plurality of circuit slices that are connected in parallel and switchably coupled to the output node of the attenuator. Each circuit slice has a tunable resistor that can be set to a conductive state ("enabled") or a high impedance state ("disabled") The number of enabled circuit slices that are connected in parallel may be used to program the attenuator gain and the attenuator impedance.

