



US 20240215423A1

(19) **United States**

(12) **Patent Application Publication**
PARK et al.

(10) **Pub. No.: US 2024/0215423 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **DISPLAY DEVICE**

Publication Classification

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.,**
YONGIN-SI (KR)

(51) **Int. Cl.**
H10K 59/88 (2006.01)
H10K 50/844 (2006.01)
H10K 59/122 (2006.01)
H10K 77/10 (2006.01)

(72) Inventors: **JUNHYUN PARK, YONGIN-SI (KR);**
SUNKWANG KIM, YONGIN-SI (KR);
KANGMOON JO, YONGIN-SI, GYEONGGI-DO (KR)

(52) **U.S. Cl.**
CPC **H10K 59/88** (2023.02); **H10K 50/844**
(2023.02); **H10K 59/122** (2023.02); **H10K**
77/10 (2023.02)

(21) Appl. No.: **18/598,391**

(22) Filed: **Mar. 7, 2024**

Related U.S. Application Data

(63) Continuation of application No. 18/313,198, filed on May 5, 2023, which is a continuation of application No. 17/170,313, filed on Feb. 8, 2021, now Pat. No. 11,653,549, which is a continuation of application No. 16/376,608, filed on Apr. 5, 2019, now Pat. No. 10,916,595.

Foreign Application Priority Data

(30) Jul. 6, 2018 (KR) 10-2018-0078935

(57) **ABSTRACT**

A display device includes a substrate, a first insulating layer disposed on the substrate, a through portion passing through the substrate and the first insulating layer, a display unit disposed on the first insulating layer and including a plurality of pixels surrounding at least a portion of the through portion, and a dummy pixel unit. Each pixel includes a light-emitting element including a pixel electrode and an opposite electrode facing each other, and an emission layer disposed between the pixel electrode and the opposite electrode. The dummy pixel unit includes a plurality of dummy pixels disposed between the through portion and the display unit, and including a metal pattern including a same material as the pixel electrode. The dummy pixels are disposed adjacent to the display unit.

