

US 20240235290A9

(19) United States

(12) Patent Application Publication JOZAKI et al.

(10) Pub. No.: US 2024/0235290 A9

(48) **Pub. Date: Jul. 11, 2024 CORRECTED PUBLICATION**

(54) **ROTOR**

(71) Applicants: TOYOTA JIDOSHA KABUSHIKI
KAISHA, Toyota-shi, Aichi-ken (JP);
AISIN CORPORTION, Kariya-shi,

Aichi-ken (JP)

(72) Inventors: Ken JOZAKI, Toyota-shi (JP);
Toshinori OKOCHI, Toyota-shi (JP);
Yoshizumi KITAHARA, Toyota-shi
(JP); Takahiro ODAGI, Kariya-shi
(JP); Masayuki IKEMOTO, Kariya-shi

(JP)

(73) Assignees: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi, Aichi-ken (JP); **AISIN CORPORTION**, Kariya-shi,

Aichi-ken (JP)

(21) Appl. No.: 18/277,154
(22) PCT Filed: Feb. 15, 2022

(86) PCT No.: **PCT/JP2022/005829**

§ 371 (c)(1),

(2) Date: Aug. 14, 2023

Prior Publication Data

(15) Correction of US 2024/0136871 A1 Apr. 25, 2024 See (22) PCT Filed.

(65) US 2024/0136871 A1 Apr. 25, 2024

(30) Foreign Application Priority Data

Feb. 16, 2021 (JP) 2021-022727

Publication Classification

(51) **Int. Cl. H02K 1/276** (2006.01)

(52) U.S. Cl.

CPC *H02K 1/276* (2013.01); *H02K 29/03* (2013.01)

(57) ABSTRACT

A rotor used for a motor includes a rotor core, and a plurality of permanent magnets embedded in a corresponding plurality of embedding holes in the rotor core configured to include flux barriers at both ends of the plurality of embedding holes in the rotor core and to include a plurality of magnetic poles. The rotor core includes a plurality of grooves on an outer peripheral surface, the plurality of grooves, with the two paired grooves, are away from an axis that becomes the q-axis when the motor is operated, and are arranged symmetrically about the axis, and the rotor core has such a cross-section that a first angle between two lines passing through the two grooves and the center of the rotor core is smaller than a second angle between the axis-side end face of the two flux barriers adjacent to each other across the axis.

