



US 20230232003A1

(19) **United States**(12) **Patent Application Publication**
DE LAGRANGE et al.(10) **Pub. No.: US 2023/0232003 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **SINGLE-INDEX QUANTIZATION MATRIX
DESIGN FOR VIDEO ENCODING AND
DECODING****Publication Classification**

(51) **Int. Cl.**
H04N 19/126 (2006.01)
H04N 19/70 (2006.01)
(52) **U.S. Cl.**
CPC **H04N 19/126** (2014.11); **H04N 19/70**
(2014.11)

(71) Applicant: **InterDigital VC Holdings France,
SAS, Cesson-Sevigne (FR)**
(72) Inventors: **Philippe DE LAGRANGE,**
Cesson-Sevigne (FR); **Fabrice
LELEANNEC,** Cesson-Sevigne (FR);
Karam NASER, Cesson-Sevigne (FR);
Edouard FRANCOIS, Cesson-Sevigne
(FR); **Pierre ANDRIVON,**
Cesson-Sevigne (FR); **Ya Chen,**
Cesson-Sevigne (FR)

(57) **ABSTRACT**

Different quantization matrices may be transmitted corresponding to different block sizes, color components and prediction modes. To more efficiently signal the coefficients of the quantization matrices, in one implementation, a unified matrix identifier matrixId is used, based on a size identifier (sizeId) that relates to CU size with larger sizes listed first, and a matrix type (matrixTypeId) with luma QMs listed first. For example, the unified identifier is derived as: matrixId=N*sizeId+matrixTypeId, where N is the number of possible type identifiers, e.g., N=6. This single identifier allows referring to any previously transmitted matrix when using prediction (copy), and transmitting larger matrices first avoids interpolation in the prediction process. When a block uses the Intra Block Copy prediction mode, QM identifier may be derived as if the block uses the INTER prediction mode.

(21) Appl. No.: **17/603,168**(22) PCT Filed: **Jun. 16, 2020**(86) PCT No.: **PCT/EP2020/066614**

§ 371 (c)(1),

(2) Date: **Oct. 12, 2021**(30) **Foreign Application Priority Data**

Jun. 21, 2019 (EP) 19305802.1

Jun. 24, 2019 (EP) 19305826.0

