



US 20240237500A9

(19) **United States**  
(12) **Patent Application Publication**  
**SONG et al.**

(10) **Pub. No.: US 2024/0237500 A9**  
(48) **Pub. Date: Jul. 11, 2024**  
**CORRECTED PUBLICATION**

(54) **DISPLAY DEVICE**

**Publication Classification**

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si (KR)  
(72) Inventors: **Jinouk SONG**, Yongin-si (KR); **Ilhoo PARK**, Yongin-si (KR); **Jin Sook BANG**, Yongin-si (KR); **Sang Hoon YIM**, Yongin-si (KR); **Seong Jin JEONG**, Yongin-si (KR)

(51) **Int. Cl.**  
**H10K 59/80** (2006.01)  
**H10K 59/122** (2006.01)  
**H10K 59/40** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **H10K 59/8791** (2023.02); **H10K 59/122** (2023.02); **H10K 59/40** (2023.02); **H10K 59/873** (2023.02); **H10K 59/879** (2023.02)

(21) Appl. No.: **18/458,852**

(57) **ABSTRACT**

(22) Filed: **Aug. 30, 2023**

**Prior Publication Data**

(15) Correction of US 2024/0138242 A1 Apr. 25, 2024  
See (22) Filed.  
See (30) Foreign Application Priority Data.

(65) US 2024/0138242 A1 Apr. 25, 2024

**Foreign Application Priority Data**

Oct. 20, 2022 (KR) ..... 10-2022-0135708

A display device according to an embodiment includes: a substrate; a transistor on the substrate; a pixel electrode electrically connected to the transistor; a pixel defining layer on the pixel electrode and having a first opening overlapping the pixel electrode; an emission layer on the pixel electrode; a common electrode on the pixel definition layer and the emission layer; an encapsulation layer on the common electrode; a light extraction pattern on the encapsulation layer and having a first refractive index; and a reflection control layer covering the light extraction pattern and having a second refractive index different from the first refractive index.

