



US 20240213526A1

(19) **United States**

(12) **Patent Application Publication**  
**Ku et al.**

(10) **Pub. No.: US 2024/0213526 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ALL-SOLID SECONDARY BATTERY AND  
METHOD OF PREPARING THE SAME**

**H01M 4/583** (2006.01)

**H01M 4/62** (2006.01)

(71) Applicant: **Samsung SDI Co., Ltd.**, Yongin-si  
(KR)

(52) **U.S. Cl.**  
**CPC** ..... **H01M 10/0562** (2013.01); **H01M 4/364**  
(2013.01); **H01M 4/583** (2013.01); **H01M**  
**4/623** (2013.01); **H01M 2004/028** (2013.01)

(72) Inventors: **Junhwan Ku**, Suwon-si (KR); **Seoksoo**  
**Lee**, Suwon-si (KR); **Moonjoo Lee**,  
Suwon-si (KR); **Yonggun Lee**,  
Suwon-si (KR); **Wonsung Choi**,  
Suwon-si (KR)

(57) **ABSTRACT**

A positive electrode for an all-solid secondary battery, including a first positive active material, a second positive active material, a first solid electrolyte, and a second solid electrolyte, wherein the first positive active material has a D50 particle diameter that is greater than a D50 particle diameter of the second positive active material, the first solid electrolyte has a first D50 particle diameter of about 0.5 to about 1.9 micrometers ( $\mu\text{m}$ ), and a particle size distribution that satisfies Equation 1 as described herein, the second solid electrolyte has second D50 particle diameter of about 2 to about 5  $\mu\text{m}$ , a ratio of the first D50 particle diameter to the second D50 particle diameter satisfies Equation 2 as described herein, and an amount of the first solid electrolyte in the positive electrode is greater than an amount of the second solid electrolyte in the positive electrode, by weight.

(21) Appl. No.: **18/524,090**

(22) Filed: **Nov. 30, 2023**

(30) **Foreign Application Priority Data**

Dec. 14, 2022 (KR) ..... 10-2022-0174955

Nov. 27, 2023 (KR) ..... 10-2023-0166676

**Publication Classification**

(51) **Int. Cl.**  
**H01M 10/0562** (2006.01)  
**H01M 4/36** (2006.01)

