

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0369508 A1 Mounioloux

(43) **Pub. Date:**

Nov. 17, 2022

(54) PUMP-DRIVEN COOLANT FILLING DEVICE AND METHODS

(71) Applicant: Rouchon Industries Inc. d/b/a Swiftech, Pico Rivera, CA (US)

Stephen Mounioloux, Pico Rivera, CA

(US)

(21) Appl. No.: 17/516,075

(22) Filed: Nov. 1, 2021

Related U.S. Application Data

(62) Division of application No. 17/322,596, filed on May 17, 2021, now Pat. No. 11,172,592.

Publication Classification

(51)	Int. Cl.	
	H05K 7/20	(2006.01)
	F04D 29/42	(2006.01)
	F04D 1/00	(2006.01)
	F04D 29/22	(2006.01)
	F04D 29/40	(2006.01)
	F04D 13/02	(2006.01)
	F04D 29/00	(2006.01)
	H05K 5/02	(2006.01)

(52) U.S. Cl.

CPC H05K 7/20272 (2013.01); F04D 29/4293 (2013.01); F04D 1/00 (2013.01); H05K 7/20327 (2013.01); F04D 29/2222 (2013.01); F04D 29/40 (2013.01); F04D 29/22 (2013.01); F04D 13/021 (2013.01); F04D 29/007 (2013.01); H05K 5/023 (2013.01); F04D 29/005 (2013.01); F04D 29/00 (2013.01); F04D 5/007 (2013.01)

(57)ABSTRACT

A system for cooling a circuit component on an electronic device includes a closed-loop cooling circuit and a coolant filling device. The closed-loop cooling circuit includes a coolant block, a first pump and a radiator. The coolant filling device includes a container, a base and a second pump disposed inside the base. The coolant filling device is configured for attachment to the cooling circuit. In some embodiments, when the coolant filling device is attached to the cooling circuit, coolant may be circulated from the coolant filling device to the cooling circuit while the cooling circuit circulates coolant. In further embodiments, when the coolant filling device is attached to the cooling circuit, coolant may be circulated from the coolant filling device to the cooling circuit while the electronic device remains powered on.

