



US 20240213506A1

(19) **United States**

(12) **Patent Application Publication**

Lee et al.

(10) **Pub. No.: US 2024/0213506 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **METHOD AND APPARATUS FOR ENTERING A STANDARD STATE FOR VANADIUM-BASED BATTERIES**

(71) Applicant: **STANDARD ENERGY INC.**, Daejeon (KR)

(72) Inventors: **Dong Young Lee**, Daejeon (KR); **Bu Gi Kim**, Daejeon (KR)

(73) Assignee: **STANDARD ENERGY INC.**, Daejeon (KR)

(21) Appl. No.: **18/396,631**

(22) Filed: **Dec. 26, 2023**

(30) **Foreign Application Priority Data**

Dec. 27, 2022 (KR) 10-2022-0185854

Publication Classification

(51) **Int. Cl.**

H01M 8/04992 (2006.01)

G01R 31/3835 (2006.01)

H01M 8/04537 (2006.01)

H01M 8/04746 (2006.01)

H01M 8/18 (2006.01)

(52) **U.S. Cl.**

CPC **H01M 8/04992** (2013.01); **G01R 31/3835**

(2019.01); **H01M 8/04559** (2013.01); **H01M**

8/04753 (2013.01); **H01M 8/188** (2013.01)

(57)

ABSTRACT

At least some embodiments herein are related to a semiconductor chip assembly comprising: a memory containing information related to entering a standard state for a vanadium-based battery; and a processor, operatively connected with the memory, that provides instructions or commands related to entering the standard state for the vanadium-based battery, by setting a constant temperature that is used in performing open circuit voltage (OCV) measurements, by setting one or more voltage values with respect to a particular voltage region that is used in performing the OCV measurements, and maintaining an equilibrium state of the vanadium-based battery while performing the OCV measurements. Also disclosed is a method comprising: entering a standard state for a vanadium-based battery and maintaining an equilibrium state of the vanadium-based battery while performing the OCV measurements. Additionally disclosed is a system comprising: at least one energy storage component having a plurality of vanadium-based batteries arranged in cells or packs; and a battery management component, operatively connected with the energy storage component, to provide battery management control for entering a standard state for the energy storage component.

