



US 20220386432A1

(19) **United States**

(12) **Patent Application Publication**
Gredler et al.

(10) **Pub. No.: US 2022/0386432 A1**

(43) **Pub. Date: Dec. 1, 2022**

(54) **LOAD CONTROL DEVICE FOR A
LIGHT-EMITTING DIODE LIGHT SOURCE**

(60) Provisional application No. 61/828,337, filed on May 29, 2013.

(71) Applicant: **Lutron Technology Company LLC,**
Coopersburg, PA (US)

Publication Classification

(72) Inventors: **Timothy P. Gredler,** Center Valley, PA (US); **Matthew R. Zartman,** Bethlehem, PA (US)

(51) **Int. Cl.**
H05B 45/3725 (2006.01)
H05B 45/10 (2006.01)
H05B 45/395 (2006.01)
H05B 45/335 (2006.01)
H05B 45/375 (2006.01)
H05B 45/385 (2006.01)

(73) Assignee: **Lutron Technology Company LLC,**
Coopersburg, PA (US)

(52) **U.S. Cl.**
CPC **H05B 45/3725** (2020.01); **H05B 45/10** (2020.01); **H05B 45/395** (2020.01); **H05B 45/335** (2020.01); **H05B 45/375** (2020.01); **H05B 45/385** (2020.01)

(21) Appl. No.: **17/881,774**

(22) Filed: **Aug. 5, 2022**

Related U.S. Application Data

(63) Continuation of application No. 17/001,050, filed on Aug. 24, 2020, now Pat. No. 11,412,593, which is a continuation of application No. 16/601,845, filed on Oct. 15, 2019, now Pat. No. 10,757,773, which is a continuation of application No. 16/378,134, filed on Apr. 8, 2019, now Pat. No. 10,448,473, which is a continuation of application No. 15/953,812, filed on Apr. 16, 2018, now Pat. No. 10,257,897, which is a continuation of application No. 15/717,123, filed on Sep. 27, 2017, now Pat. No. 9,949,330, which is a continuation of application No. 15/460,973, filed on Mar. 16, 2017, now Pat. No. 9,814,112, which is a continuation of application No. 15/291,308, filed on Oct. 12, 2016, now Pat. No. 9,635,726, which is a continuation of application No. 14/796,278, filed on Jul. 10, 2015, now Pat. No. 9,497,817, which is a continuation of application No. 14/290,584, filed on May 29, 2014, now Pat. No. 9,113,521.

(57) **ABSTRACT**

A load control device for controlling the intensity of a lighting load, such as a light-emitting diode (LED) light source, may include a power converter circuit operable to receive a rectified AC voltage and to generate a DC bus voltage, a load regulation circuit operable to receive the bus voltage and to control the magnitude of a load current conducted through the lighting load, and a control circuit operatively coupled to the load regulation circuit for pulse width modulating or pulse frequency modulating the load current to control the intensity of the lighting load to a target intensity. The control circuit may control the intensity of the lighting load by pulse width modulating the load current when the target intensity is above a predetermined threshold and control the intensity of the lighting load by pulse frequency modulating the load current when the target intensity is below the predetermined threshold.

