



US 20240213473A1

(19) **United States**

(12) **Patent Application Publication**
Kim et al.

(10) **Pub. No.: US 2024/0213473 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ANODE-SOLID ELECTROLYTE
SUB-ASSEMBLY FOR ALL-SOLID
SECONDARY BATTERY, ALL-SOLID
SECONDARY BATTERY INCLUDING THE
SAME, AND PREPARATION METHOD
THEREOF**

(71) Applicants: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR); **UIF (University
Industry Foundation)**, Yonsei
University, Seoul (KR)

(72) Inventors: **Kyoungwan Kim**, Suwon-si (KR);
Jonghyeok Park, Seoul (KR);
Yonggun Lee, Suwon-si (KR);
Kwanghee Kim, Seoul (KR); **Jusik
Kim**, Suwon-si (KR)

(21) Appl. No.: **18/539,499**

(22) Filed: **Dec. 14, 2023**

(30) **Foreign Application Priority Data**

Dec. 15, 2022 (KR) 10-2022-0176246
Nov. 21, 2023 (KR) 10-2023-162709

Publication Classification

(51) **Int. Cl.**
H01M 4/583 (2006.01)
H01M 4/04 (2006.01)
H01M 4/70 (2006.01)
H01M 10/0562 (2006.01)
(52) **U.S. Cl.**
CPC **H01M 4/583** (2013.01); **H01M 4/0407**
(2013.01); **H01M 4/70** (2013.01); **H01M**
10/0562 (2013.01); **H01M 2004/021** (2013.01)

(57) **ABSTRACT**

An anode-solid electrolyte sub-assembly for an all-solid secondary battery, the anode-solid electrolyte sub-assembly including: an anode current collector; a mixed ionic-electronic conductor structure disposed on a first side of the anode current collector, the mixed ionic-electronic conductor structure containing a mixed ionic-electronic conductor, and having a plurality of openings extending along a thickness direction; wherein the plurality of openings has a structure in which at least one end is open; an interlayer disposed on the mixed ionic-electronic conductor structure and opposite the anode current collector; and a solid electrolyte disposed on the interlayer and opposite the mixed ionic-electronic conductor structure, wherein the interlayer includes an interlayer material.

