



US 20230232678A1

(19) **United States**(12) **Patent Application Publication**
CHO et al.(10) **Pub. No.: US 2023/0232678 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **DISPLAY DEVICE**(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si (KR)(72) Inventors: **Jaehyung CHO**, Yongin-si (KR);
Seonyoung CHOI, Yongin-si (KR)(21) Appl. No.: **18/075,823**(22) Filed: **Dec. 6, 2022**(30) **Foreign Application Priority Data**

Jan. 18, 2022 (KR) 10-2022-0007347

Publication Classification(51) **Int. Cl.**
H10K 59/131 (2006.01)
G09G 3/3233 (2006.01)(52) **U.S. Cl.**CPC **H01L 27/3276** (2013.01); **G09G 3/3233**
(2013.01); **H01L 27/3211** (2013.01)(57) **ABSTRACT**

A display device includes a substrate which includes a display area and in which a first opening area is defined, and a non-display area which includes a first driving circuit area and a second driving circuit area adjacent to the first driving circuit area, and in which a second opening area is defined between the first driving circuit area and the second driving circuit area, and a circuit layer disposed on the substrate and including a first driving circuit overlapping the first driving circuit area and including a first conductive pattern and a second driving circuit overlapping the second driving circuit area and including a second conductive pattern. A shape of the first conductive pattern and a shape of the second conductive pattern are inverted from each other based on a first virtual straight line passing through a center of the first driving circuit area and a center of the second driving circuit area in a plan view.

