



US 20240213856A1

(19) **United States**

(12) **Patent Application Publication**
Dauth et al.

(10) **Pub. No.: US 2024/0213856 A1**

(43) **Pub. Date: Jun. 27, 2024**

(54) **ASSEMBLY, DRIVE DEVICE**

Publication Classification

(71) Applicant: **Robert Bosch GmbH**, Stuttgart (DE)

(51) **Int. Cl.**

H02K 11/00 (2006.01)

H01R 13/52 (2006.01)

H02K 11/21 (2006.01)

(72) Inventors: **Robert Alexander Dauth**, Heilbronn (DE); **Benjamin Haufe**, Obersulm Willsbach (DE); **Janos Tamas Csoti**, Erligheim (DE)

(52) **U.S. Cl.**

CPC **H02K 11/0094** (2013.01); **H01R 13/5221** (2013.01); **H02K 11/21** (2016.01); **H02K 2211/03** (2013.01)

(21) Appl. No.: **18/557,399**

(22) PCT Filed: **Aug. 10, 2022**

(86) PCT No.: **PCT/EP2022/072476**

§ 371 (c)(1),

(2) Date: **Oct. 26, 2023**

(30) **Foreign Application Priority Data**

Aug. 19, 2021 (DE) 10 2021 209 101.6

(57)

ABSTRACT

An assembly. The assembly includes a first element and a second element, wherein the elements are fastened to one another in such a way that they together enclose an assembly interior, and wherein an electrically conductive cable protrudes into the assembly interior through a cable passage formed between the elements. For forming a particle seal assigned to the cable passage, at least one of the elements has at least one projection, which projects in the direction of the other element and presses the cable against the other element.

