US 20230231331A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2023/0231331 A1**

Chapeau (43) **Pub. Date: Jul. 20, 2023**

(54) **MAGNETIC ELECTRICAL PLUG INTERFACE**

(71) Applicant: **Carrier Corporation**, Palm Beach Gardens, FL (US)

(72) Inventor: **Lucas Chapeau**, Isneauville (FR)

(21) Appl. No.: **18/155,422**

(22) Filed: **Jan. 17, 2023**

(30) **Foreign Application Priority Data**

Jan. 17, 2022 (EP) 22151886.3

Publication Classification

(51) **Int. Cl.**

H01R 11/30 (2006.01)

B60L 53/16 (2006.01)

(52) **U.S. Cl.**

CPC ***H01R 11/30*** (2013.01); ***B60L 53/16*** (2019.02); *H01R 2201/26* (2013.01)

(57) **ABSTRACT**

A magnetic electrical plug interface for charging a transport refrigeration unit, TRU. The magnetic electrical plug interface includes a first electrical connector and a second electrical connector. The first electrical connector includes: a socket having a closed end and an open end; a first magnetic body including a first electrical contact, the first magnetic body is slidable in the socket; a resilient biasing element configured to bias the first magnetic body towards the closed end of the socket; and a second electrical contact fixed towards the open end of the socket. The second electrical connector includes: a second magnetic body including a third electrical contact. In an unplugged configuration in which the first electrical connector is disengaged from the second electrical connector, the resilient biasing element is configured to maintain a separation between the first electrical contact and the second electrical contact.