



US 20240237445A1

(19) **United States**

(12) **Patent Application Publication**  
**YAMAZAKI et al.**

(10) **Pub. No.: US 2024/0237445 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **Semiconductor Energy Laboratory Co., Ltd.**, Atsugi-shi (JP)

(72) Inventors: **Shunpei YAMAZAKI**, Setagaya (JP);  
**Kensuke YOSHIZUMI**, Isehara (JP)

(21) Appl. No.: **18/614,822**

(22) Filed: **Mar. 25, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 18/143,182, filed on May 4, 2023, now Pat. No. 11,950,474, which is a continuation of application No. 17/523,153, filed on Nov. 10, 2021, now Pat. No. 11,678,538, which is a continuation of application No. 16/884,369, filed on May 27, 2020, now Pat. No. 11,271,070, which is a continuation of application No. 16/211,763, filed on Dec. 6, 2018, now Pat. No. 10,680,055, which is a continuation of application No. 15/670,309, filed on Aug. 7, 2017, now Pat. No. 10,263,063, which is a continuation of application No. 15/363,228, filed on Nov. 29, 2016, now Pat. No. 10,096,669, which is a continuation of application No. 14/192,178, filed on Feb. 27, 2014, now Pat. No. 9,543,533.

**Foreign Application Priority Data**

Mar. 7, 2013 (JP) ..... 2013-045119

**Publication Classification**

(51) **Int. Cl.**  
**H10K 59/131** (2023.01)  
**G04G 9/00** (2006.01)

**H10K 59/121** (2023.01)

**H10K 77/10** (2023.01)

**H01L 27/12** (2006.01)

**H05K 1/02** (2006.01)

**H05K 1/14** (2006.01)

**H05K 1/18** (2006.01)

**H10K 59/12** (2023.01)

**H10K 102/00** (2023.01)

(52) **U.S. Cl.**

**CPC** ..... **H10K 59/131** (2023.02); **G04G 9/0088** (2013.01); **H10K 59/1213** (2023.02); **H10K 77/111** (2023.02); **H01L 27/1244** (2013.01); **H05K 1/0277** (2013.01); **H05K 1/028** (2013.01); **H05K 1/0283** (2013.01); **H05K 1/147** (2013.01); **H05K 1/189** (2013.01); **H05K 2201/05** (2013.01); **H05K 2201/051** (2013.01); **H05K 2201/052** (2013.01); **H05K 2201/053** (2013.01); **H05K 2201/055** (2013.01); **H10K 59/1201** (2023.02); **H10K 2102/311** (2023.02); **Y02E 10/549** (2013.01)

(57)

**ABSTRACT**

One embodiment of the present invention provides a highly reliable display device. In particular, a display device to which a signal or a power supply potential can be supplied stably is provided. Further, a bendable display device to which a signal or a power supply potential can be supplied stably is provided. The display device includes, over a flexible substrate, a display portion, a plurality of connection terminals to which a signal from an outside can be input, and a plurality of wirings. One of the plurality of wirings electrically connects one of the plurality of connection terminals to the display portion. The one of the plurality of wirings includes a first portion including a plurality of separate lines and a second portion in which the plurality of lines converge.

