



US 20230232669A1

(19) **United States**(12) **Patent Application Publication****Kim et al.**(10) **Pub. No.: US 2023/0232669 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE DISPLAY DEVICE****H10K 59/60** (2006.01)**H01L 31/054** (2006.01)(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)(52) **U.S. Cl.**CPC ..... **H10K 59/124** (2023.02); **H10K 59/1201** (2023.02); **H10K 59/8731** (2023.02); **H10K 59/60** (2023.02); **H01L 31/0547** (2014.12); **H10K 59/8791** (2023.02); **H10K 59/353** (2023.02)(72) Inventors: **Kyungmin Kim**, Yongin-si (KR);  
**Junhyeong Park**, Yongin-si (KR);  
**Dongwon Kim**, Yongin-si (KR)(21) Appl. No.: **18/154,696**(22) Filed: **Jan. 13, 2023**(30) **Foreign Application Priority Data**

Jan. 14, 2022 (KR) ..... 10-2022-0006173

**Publication Classification**(51) **Int. Cl.****H10K 59/124** (2006.01)**H10K 59/12** (2006.01)**H10K 59/80** (2006.01)

(57)

**ABSTRACT**

A display device and a method of manufacturing the display device are provided. The display device includes a substrate including a transmissive display area including a first pixel area, a second pixel area, and an opening area between the first pixel area and the second pixel area and defining a substrate opening portion, a light-emitting element layer above the substrate and including a first light-emitting element in the first pixel area and a second light-emitting element in the second pixel area, and a first inorganic encapsulation layer above the light-emitting element layer and extending from the first pixel area to the second pixel area across the substrate opening portion.

