

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0213203 A1 ZHENG et al.

Jun. 27, 2024 (43) Pub. Date:

(54) CHIP PACKAGE STRUCTURE, PRODUCTION METHOD FOR CHIP PACKAGE STRUCTURE, AND ELECTRONIC DEVICE

(71) Applicant: HUAWEI TECHNOLOGIES CO.,

LTD., Shenzhen (CN)

(72) Inventors: Yonggang ZHENG, Dongguan (CN);

Ran JIANG, Dongguan (CN); Zikai TANG, Dongguan (CN); Yanghua LI, Dongguan (CN); Shujun HUANG,

Dongguan (CN)

(21) Appl. No.: 18/599,469

(22) Filed: Mar. 8, 2024

Related U.S. Application Data

Continuation of application No. PCT/CN2022/ 114108, filed on Aug. 23, 2022.

(30)Foreign Application Priority Data

(CN) 202111063937.X

Publication Classification

(51) Int. Cl. H01L 23/00 (2006.01)H01L 23/31 (2006.01) (52) U.S. Cl.

CPC H01L 24/20 (2013.01); H01L 23/3121 (2013.01); H01L 24/19 (2013.01); H01L 24/24 (2013.01); H01L 24/32 (2013.01); H01L 2224/19 (2013.01); H01L 2224/211 (2013.01); H01L 2224/214 (2013.01); H01L 2224/24226 (2013.01); H01L 2224/24246 (2013.01); H01L 2224/32225 (2013.01); H01L 2224/32245 (2013.01)

(57)ABSTRACT

The technology of this application relates to a chip package structure, a production method for a chip package structure, and an electronic device. The chip package structure includes a first connection layer having an upper surface and a lower surface that are opposite to each other, a die disposed on the upper surface of the first connection layer, a first conduction structure disposed on an upper surface of the die, a first plastic package layer covering the die and the first conduction structure, and a rewiring layer disposed on the first plastic package layer. At least a part of the first conduction structure is exposed from an upper surface of the first plastic package layer. The rewiring layer is coupled to the first conduction structure. A signal of the die can be directly led out through the first conduction structure and the rewiring layer.

