



US 20240244895A1

(19) **United States**

(12) **Patent Application Publication**
TANG

(10) **Pub. No.: US 2024/0244895 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **OLED DISPLAY PANEL AND
MANUFACTURING METHOD THEREOF**

H10K 59/122 (2006.01)

H10K 59/131 (2006.01)

H10K 59/38 (2006.01)

H10K 59/80 (2006.01)

(71) Applicant: **SHENZHEN CHINA STAR
OPTOELECTRONICS
SEMICONDUCTOR DISPLAY
TECHNOLOGY CO., LTD.**, Shenzhen
(CN)

(52) **U.S. Cl.**

CPC *H10K 59/124* (2023.02); *H10K 59/1201*

(2023.02); *H10K 59/122* (2023.02); *H10K*

59/131 (2023.02); *H10K 59/38* (2023.02);

H10K 59/878 (2023.02)

(72) Inventor: **Jia TANG**, Shenzhen (CN)

(21) Appl. No.: **17/771,651**

(57)

ABSTRACT

(22) PCT Filed: **Apr. 22, 2022**

(86) PCT No.: **PCT/CN2022/088407**

§ 371 (c)(1),

(2) Date: **Apr. 25, 2022**

(30) **Foreign Application Priority Data**

Apr. 12, 2022 (CN) 202210382743.4

Publication Classification

(51) **Int. Cl.**

H10K 59/124 (2006.01)

H10K 59/12 (2006.01)

Embodiments of the present application disclose an OLED display panel and a method of manufacturing an OLED display panel. The OLED display panel includes an array substrate and a multi-functional layer disposed on the array substrate. The multi-functional layer includes a plurality of conductive portions disposed at intervals and non-conductive portions. One end of the conductive portions is electrically connected to a light emitting layer, and the other end of the conductive portions is electrically connected to a source. The conductive portions and the non-conductive portions are located at a same layer, are coplanar, and are manufactured in a single process. This can reduce at least one mask, and the cost is lowered.

