

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0244912 A1 Deng et al.

(43) Pub. Date:

Jul. 18, 2024

(54) DISPLAY SUBSTRATE AND DISPLAY DEVICE

(71) Applicants: Chengdu BOE Optoelectronics Technology Co., Ltd., Chengdu (CN); BOE Technology Group Co., Ltd., Beijing (CN)

(72) Inventors: Jiangtao Deng, Beijing (CN); Yan Huang, Beijing (CN); Chi Yu, Beijing (CN); Biao Liu, Beijing (CN); Jianchang Cai, Beijing (CN); Xiaoqing Shu, Beijing (CN); Yi Zhang, Beijing (CN)

(21) Appl. No.: 18/260,684

(22) PCT Filed: Aug. 22, 2022

PCT/CN2022/113886 (86) PCT No.:

§ 371 (c)(1),

(2) Date: Jul. 7, 2023

(30)Foreign Application Priority Data

Aug. 23, 2021	(CN)	 202110971715.1
May 13, 2022	(CN)	 202210531683.8

Publication Classification

(51) Int. Cl. H10K 59/35 (2006.01)H10K 59/122 (2006.01)H10K 59/131 (2006.01)H10K 59/65 (2006.01)

(52) U.S. Cl.

CPC H10K 59/353 (2023.02); H10K 59/122 (2023.02); H10K 59/131 (2023.02); H10K 59/352 (2023.02); H10K 59/65 (2023.02)

ABSTRACT (57)

A display substrate and a display device. The display substrate includes: a first pixel structure including a first subpixel and a second sub-pixel; and a pixel defining layer including first openings and second openings, where the first sub-pixel includes the first opening, and the second subpixel includes the second opening. In the first pixel structure, a pattern of an orthographic projection of the first opening of the at least one first sub-pixel on the base substrate has a maximum size in the first direction, a pattern of an orthographic projection of the second opening of the at least one second sub-pixel on the base substrate has a maximum size in the second direction, an angle is formed between the second direction and the first direction, and a ratio of the maximum size of the first opening to the maximum size of the second opening ranges from 0.2 to 2.

