



US 20240224413A1

(19) **United States**

(12) **Patent Application Publication**
URASHIMA et al.

(10) **Pub. No.: US 2024/0224413 A1**

(43) **Pub. Date: Jul. 4, 2024**

(54) **WIRING SUBSTRATE**

(71) Applicant: **Resonac Corporation**, Minato-ku,
Tokyo (JP)

(72) Inventors: **Kosuke URASHIMA**, Minato-ku,
Tokyo (JP); **Motoki YONEKURA**,
Minato-ku, Tokyo (JP); **Motohiro**
ARIFUKU, Minato-ku, Tokyo (JP);
Tomohiko KOTAKE, Minato-ku,
Tokyo (JP); **Etsuo MIZUSHIMA**,
Minato-ku, Tokyo (JP)

(21) Appl. No.: **18/555,866**

(22) PCT Filed: **Nov. 16, 2021**

(86) PCT No.: **PCT/JP2021/042015**

§ 371 (c)(1),

(2) Date: **Dec. 18, 2023**

(30) **Foreign Application Priority Data**

Apr. 21, 2021 (JP) 2021-071939

Publication Classification

(51) **Int. Cl.**

H05K 1/02 (2006.01)

H05K 3/06 (2006.01)

H05K 3/28 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 1/0237** (2013.01); **H05K 3/06**
(2013.01); **H05K 3/28** (2013.01); **H05K**
2201/0753 (2013.01); **H05K 2201/083**
(2013.01); **H05K 2201/10287** (2013.01); **H05K**
2203/063 (2013.01)

(57)

ABSTRACT

A wiring substrate includes a substrate, conductor wiring provided on the substrate, and an insulator positioned on at least a part of the periphery of the conductor wiring, in which the insulator contains a magnetic material. The wiring substrate ensures little loss in transmission even in high-frequency band.

