

US 20240237556A9

(19) United States

(12) Patent Application Publication Lei et al.

(54) MULTIMODE SUPERCONDUCTING CAVITY RESONATORS

(71) Applicant: Yale University, New Haven, CT (US)

(72) Inventors: Chan U Lei, Stamford, CT (US);
Suhas Ganjam, Fairfield, CA (US);
Lev Krayzman, New Haven, CT (US);
Robert J. Schoelkopf Ill, Madison, CT (US); Luigi Frunzio, North Haven, CT (US)

(73) Assignee: Yale University, New Haven, CT (US)

(21) Appl. No.: 18/277,505

(22) PCT Filed: Feb. 17, 2022

(86) PCT No.: **PCT/US2022/016733**

§ 371 (c)(1),

(2) Date: **Aug. 16, 2023**

Prior Publication Data

(15) Correction of US 2024/0138269 A1 Apr. 25, 2024 See (86) PCT No.

(65) US 2024/0138269 A1 Apr. 25, 2024

(10) Pub. No.: US 2024/0237556 A9

(48) **Pub. Date: Jul. 11, 2024 CORRECTED PUBLICATION**

Related U.S. Application Data

(60) Provisional application No. 63/150,955, filed on Feb. 18, 2021.

Publication Classification

(51) Int. Cl. H10N 60/80 (2006.01) G06N 10/40 (2006.01) H10N 60/12 (2006.01) H10N 60/85 (2006.01)

(52) U.S. Cl.

CPC H10N 60/805 (2023.02); G06N 10/40 (2022.01); H10N 60/12 (2023.02); H10N 60/85 (2023.02)

(57) ABSTRACT

Techniques are described to construct an electromagnetic resonator by arranging a resonant structure within a superconducting cavity. The architecture of the design may provide a low loss superconducting cavity resonator that may exhibit multiple modes. The multimode nature of this resonator is produced in part by the resonant structure in such a way that allows the modes of the resonant structure rather than by having to alter the physical dimensions of the cavity, as would otherwise be required in a conventional superconducting cavity resonator. In some embodiments, the resonant structure may include a suspended superconductor comprising metal and/or metallized parts.



