US 20230231623A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2023/0231623 A1**

(43) **Pub. Date: Jul. 20, 2023**

**YOU**

(54) **METHOD AND APPARATUS FOR RETRANSMISSION IN COMMUNICATION SYSTEM**

(71) Applicant: **ELECTRONICS AND TELECOMMUNICATIONS RESEARCH INSTITUTE**, Daejeon (KR)

(72) Inventor: **Duk Hyun YOU**, Daejeon (KR)

(21) Appl. No.: **18/124,394**

(22) Filed: **Mar. 21, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. 17/086,724, filed on Nov. 2, 2020, now Pat. No. 11,641,235.

(30) **Foreign Application Priority Data**

Nov. 7, 2019 (KR) ..... 10-2019-0141772
Nov. 21, 2019 (KR) ..... 10-2019-0150338
Oct. 5, 2020 (KR) ..... 10-2020-0128186

**Publication Classification**

(51) **Int. Cl.**

| | |
|---|---|
| ***H04B 7/185*** | (2006.01) |
| ***H04B 7/195*** | (2006.01) |
| ***H04L 5/00*** | (2006.01) |
| ***H04L 1/1812*** | (2006.01) |
| ***H04L 1/00*** | (2006.01) |

(52) **U.S. Cl.**

CPC ..... ***H04B 7/18543*** (2013.01); ***H04B 7/195*** (2013.01); ***H04L 5/0055*** (2013.01); ***H04L 1/1819*** (2013.01); ***H04L 1/0038*** (2013.01)

(57) **ABSTRACT**

An operation method of a first communication node in a communication system may comprise receiving one or more transport blocks (TBs) from a second communication node based on transmission parameters in an aggregated transmission period #n; generating decoding results for the one or more TBs; generating information required for changing the transmission parameters based on the decoding results; and transmitting the required information to the second communication node, wherein n is a natural number.