US 20240215278A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2024/0215278 A1

MANAGAKI (43) Pub. Date: Jun. 27, 2024

(54) **DISPLAY DEVICE AND METHOD OF MANUFACTURING THE SAME**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventor: **Nobuto MANAGAKI**, Tokyo (JP)

(73) Assignee: **Japan Display Inc.**, Tokyo (JP)

(21) Appl. No.: **18/389,834**

(22) Filed: **Dec. 20, 2023**

(30) **Foreign Application Priority Data**

Dec. 26, 2022 (JP) 2022-208347
Nov. 17, 2023 (JP) 2023-195962

Publication Classification

(51) **Int. Cl.**
H10K 50/11 (2006.01)
H10K 59/12 (2006.01)

(52) **U.S. Cl.**
CPC ***H10K 50/11*** (2023.02); ***H10K 59/1201*** (2023.02); *H10K 2101/40* (2023.02)

(57) **ABSTRACT**

According to one embodiment, a display device has such configuration that each of ΔE**1**_LUMO and ΔE**1**_HOMO is 0.35 eV or less (ΔE**1**≤0.35 eV), each of ΔE**2**_LUMO and ΔE**2**_HOMO is 0.1 eV or more and 0.5 eV or less (0.1 eV≤ΔE**2**≤0.5 eV), the light emitting layer includes a first material and a second material, a band gap of the first material is larger than a band gap of the second material, and a ratio of the first material to the second material is 5% or more and less than 40%.