



US 20230231127A1

(19) **United States**

(12) **Patent Application Publication**

**WANG**

(10) **Pub. No.: US 2023/0231127 A1**

(43) **Pub. Date:** **Jul. 20, 2023**

(54) SECONDARY BATTERY AND DEVICE CONTAINING SAME

(71) Applicant: **Contemporary Amperex Technology Co., Limited**, Ningde City (CN)

(72) Inventor: **Guangjun WANG**, Ningde City (CN)

(73) Assignee: **Contemporary Amperex Technology Co., Limited**, Ningde City (CN)

(21) Appl. No.: **18/115,004**

(22) Filed: **Feb. 28, 2023**

**Related U.S. Application Data**

(63) Continuation of application No. 17/565,438, filed on Dec. 29, 2021, now Pat. No. 11,626,589.

**Foreign Application Priority Data**

Nov. 29, 2019 (CN) ..... 201911205359.1

**Publication Classification**

(51) **Int. Cl.**

**H01M 4/525** (2010.01)

**H01M 4/505** (2010.01)

**H01M 4/36** (2006.01)

**H01M 4/48** (2010.01)

**H01M 50/489** (2021.01)

**H01M 4/587** (2010.01)

**H01M 50/491** (2021.01)

**H01M 4/583** (2010.01)

**H01M 50/449** (2021.01)

**H01M 4/02** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H01M 4/525** (2013.01); **H01M 4/505** (2013.01); **H01M 4/364** (2013.01); **H01M 4/48** (2013.01); **H01M 50/489** (2021.01); **H01M 4/587** (2013.01); **H01M 50/491** (2021.01); **H01M 4/583** (2013.01); **H01M 50/449** (2021.01); **H01M 2004/028** (2013.01); **H01M 2004/027** (2013.01)

(57) **ABSTRACT**

This application discloses a secondary battery and a device containing the secondary battery. A positive active material of the secondary battery includes one or more of lithium nickel cobalt manganese oxide, lithium nickel cobalt aluminum oxide, and a modified material thereof. A negative active material of the secondary battery includes a silicon-oxygen compound and graphite. A separator of the secondary battery includes a substrate and a coating layer. The secondary battery satisfies:

$$7.5 \leq \frac{3460}{ED} - \left( D_{50} - D_C 50 \times 0.75 - \frac{T}{18} \right) \leq 11.5,$$

where  $ED \geq 270$  Wh/Kg,  $11 \mu m \leq D_{50} \leq 18.5 \mu m$ ,  $11 \mu m \leq D_C 50 \leq 20 \mu m$ . The secondary battery according to this application achieves relatively high cycle performance while achieving a relatively high energy density concurrently.

