

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0386509 A1 Zhou et al.

Dec. 1, 2022 (43) **Pub. Date:**

(54) DOUBLE-SIDED COOLING COLD PLATES WITH OVERHANGING HEAT SINKS AND THROUGH BODY BUSBAR FOR HIGH-POWER DENSITY POWER **ELECTRONICS**

(71) Applicants: TOYOTA MOTOR ENGINEERING & MANUFACTURING NORTH AMERICA, INC., PLANO, TX (US); University of Colorado Boulder, Boulder, CO (US)

(72) Inventors: Feng Zhou, Ann Arbor, MI (US); Yuqing Zhou, Ann Arbor, MI (US); Ercan Mehmet Dede, Ann Arbor, MI (US); Robert Erickson, Boulder, CO (US); Dragan Maksimovic, Boulder, CO (US); Vivek Sankaranarayanan, Boulder, CO (US); Yucheng Gao, Boulder, CO (US)

(73) Assignees: TOYOTA MOTOR ENGINEERING & MANUFACTURING NORTH **AMERICA, INC.**, PLANO, TX (US); University of Colorado Boulder, Boulder, CO (US)

(21) Appl. No.: 17/329,727

(22) Filed: May 25, 2021

Publication Classification

(51) Int. Cl. H05K 7/20 (2006.01)

U.S. Cl. (52)CPC H05K 7/20509 (2013.01); H05K 7/209 (2013.01)

(57)ABSTRACT

A double-sided cold plate includes a manifold comprising openings extending from a first surface of the manifold through the manifold to a second surface of the manifold forming recesses within the manifold and an inlet channel and an outlet channel fluidly coupled to the recesses within the manifold, a plurality of first heat sinks coupled to the first surface of the manifold enclosing the openings on the first surface, and a plurality of second heat sinks positioned adjacent each other along a length of the manifold and coupled to the second surface of the manifold, enclosing the openings on the second surface, a width of the plurality of second heat sinks is greater than a width of the manifold thereby forming an overhanging portion on each lengthwise side of the manifold, the overhanging portion configured to mechanically support a plurality of electrical components positioned around a perimeter of the manifold.

