



(19) **United States**

(12) **Patent Application Publication**  
**PARK et al.**

(10) Pub. No.: US 2024/0237460 A1

(43) **Pub. Date:** **Jul. 11, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si,  
Gyeonggi-do (KR)

(72) Inventors: **Yong Hwan PARK**, Yongin-si (KR); **Ju Yeon KIM**, Yongin-si (KR); **Sung Kyun PARK**, Yongin-si (KR); **Seung Chan LEE**, Yongin-si (KR); **Sae Young HONG**, Yongin-si (KR)

(21) Appl. No.: 18/501,889

(22) Filed: **Nov. 3, 2023**

(30) **Foreign Application Priority Data**

Jan. 6, 2023 (KR) ..... 10-2023-0002475  
Mar. 24, 2023 (KR) ..... 10-2023-0038911

### Publication Classification

(51) **Int. Cl.**  
*H10K 59/35* (2006.01)  
*H10K 59/131* (2006.01)

(52) **U.S. Cl.**  
CPC ..... *H10K 59/353* (2023.02); *H10K 59/131*  
(2023.02); *H10K 59/40* (2023.02); *H10K*  
*59/88* (2023.02); *H10K 71/621* (2023.02)

(57) **ABSTRACT**

A display device includes: a display component comprising first and second pixels; and a sensor component comprising conductive patterns. Each pixel may include first, second and third sub-pixels. The first and second pixels may be adjacent to each other. The third sub-pixel of the first pixel may be adjacent to the third sub-pixel of the second pixel. The first and second sub-pixels of the first pixel may be adjacent to the first and second sub-pixels of the second pixel. Each conductive pattern may comprise first and second sensing electrodes. The first sensing electrode may comprise first cells and a first bridge. The second sensing electrode may comprise second cells and a second bridge. The second bridge may be between the third sub-pixels of the first and second pixels, and between the second sub-pixel of the first pixel and the first sub-pixel of the second pixel.

