



US 20220369429A1

(19) **United States**(12) **Patent Application Publication**
SWIDERSKI et al.(10) **Pub. No.: US 2022/0369429 A1**(43) **Pub. Date: Nov. 17, 2022**(54) **SYSTEM AND METHOD FOR INDUCTION
SHRINK FITTING***B23P 11/02* (2006.01)*G06K 7/14* (2006.01)*G06K 19/06* (2006.01)(71) Applicant: **PRATT & WHITNEY CANADA
CORP.,** Longueuil (CA)(52) **U.S. Cl.**CPC *H05B 6/06* (2013.01); *F16B 4/006*
(2013.01); *G05D 23/1951* (2013.01); *G05D*
23/22 (2013.01); *B23P 11/025* (2013.01);
G06K 7/1417 (2013.01); *G06K 19/06037*
(2013.01)(72) Inventors: **Joseph SWIDERSKI,** Dundas (CA);
Guy BEAULIEU, Prévost (CA);
Parham ZABETI, Toronto (CA);
Pierre-Luc LACHANCE, Brossard
(CA)(57) **ABSTRACT**(21) Appl. No.: **17/321,583**(22) Filed: **May 17, 2021****Publication Classification**(51) **Int. Cl.***H05B 6/06* (2006.01)*F16B 4/00* (2006.01)*G05D 23/19* (2006.01)*G05D 23/22* (2006.01)

An induction heating system can be adapted for shrink fitting a plurality of different assemblies. A plurality of tooling units associated to respective ones of the assemblies, each one having an appropriately configured induction coil and holder, can be provided. A computer can be used to control the delivery of electrical power to the induction coil in accordance with a heating recipe, and can be provided with an input device for inputting an assembly identifier allowing the computer to operate the control based on the right heating recipe.

