



US 20220352851A1

(19) **United States**

(12) **Patent Application Publication**  
**Itasaka**

(10) **Pub. No.: US 2022/0352851 A1**

(43) **Pub. Date: Nov. 3, 2022**

(54) **CIRCUIT DEVICE AND OSCILLATOR**

(71) Applicant: **SEIKO EPSON CORPORATION**,  
Tokyo (JP)

(72) Inventor: **Yosuke Itasaka**, Kamiina-gun (JP)

(21) Appl. No.: **17/732,608**

(22) Filed: **Apr. 29, 2022**

(30) **Foreign Application Priority Data**

Apr. 30, 2021 (JP) ..... 2021-077559

**Publication Classification**

(51) **Int. Cl.**  
**H03B 5/36** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H03B 5/366** (2013.01); **H03B 5/362**  
(2013.01); **H03B 2200/0034** (2013.01)

(57) **ABSTRACT**

A circuit device includes a first terminal to be coupled to one end of a resonator, a second terminal to be coupled to another end of the resonator, an amplifying element configured to amplify a signal from the first terminal to output the signal amplified to the second terminal, a first resistor element disposed on a signal path between an input node and an output node of the amplifying element, a capacitance element disposed on a signal path between the first terminal and the input node, and a first switch element configured to switch electrical coupling between the input node and a ground.

