

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2022/0353988 A1 SASAKI et al.

Nov. 3, 2022 (43) **Pub. Date:**

(54) METAL-CLAD LAMINATE AND PRINTED WIRING BOARD

(71) Applicant: Panasonic Intellectual Property Management Co., Ltd., Osaka (JP)

(72) Inventors: **Dai SASAKI**, Fukushima (JP); Yasunori NISHIGUCHI, Osaka (JP); Kazuki MATSUMURA, Fukushima (JP); Yohsuke ISHIKAWA, Fukushima (JP); Hiroki TAMIYA, Fukushima (JP);

Koji KISHINO, Fukushima (JP)

(73) Assignee: Panasonic Intellectual Property Management Co., Ltd., Osaka (JP)

(21) Appl. No.: 17/621,011

(22) PCT Filed: Jun. 19, 2020

(86) PCT No.: PCT/JP2020/024182

§ 371 (c)(1),

(2) Date: Dec. 20, 2021

(30)Foreign Application Priority Data

Publication Classification

(51) Int. Cl. H05K 1/03 (2006.01)H05K 1/05 (2006.01)

U.S. Cl.

CPC H05K 1/036 (2013.01); H05K 1/0366 (2013.01); H05K 1/05 (2013.01); H05K 2201/0227 (2013.01); H05K 2201/0218 (2013.01); H05K 2201/0266 (2013.01)

(57)**ABSTRACT**

A metal-clad laminate includes: an insulating layer; and a metal layer stacked on the insulating layer. The insulating layer includes: a first layer; and a second layer interposed between the first layer and the metal layer. The first layer contains a cured product of a first resin composition containing composite particles. The second layer contains a cured product of a second resin composition. The first resin composition contains composite particles, each having a core containing a fluororesin and a shell containing a silicon oxide that coats the core at least partially. The second resin composition may or may not contain composite particles. When the second resin composition contains the composite particles, a ratio of the composite particles in the second resin composition to solid content of the second resin composition is lower than a ratio of the composite particles in the first resin composition to solid content of the first resin composition.

