US 20240237475A9

(19) **United States**

(12) **Patent Application Publication**

CHOI et al.

(10) **Pub. No.: US 2024/0237475 A9**

(48) **Pub. Date: Jul. 11, 2024**

CORRECTED PUBLICATION

(54) **DISPLAY DEVICE**

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**, Yongin-si (KR)

(72) Inventors: **Min Oh CHOI**, Yongin-si (KR); **Kwang Soo BAE**, Yongin-si (KR); **Gee Bum KIM**, Yongin-si (KR); **Bo Kwang SONG**, Yongin-si (KR); **Soo Yeong HONG**, Yongin-si (KR)

(21) Appl. No.: **18/225,251**

(22) Filed: **Jul. 24, 2023**

Prior Publication Data

(15) Correction of US 2024/0138229 A1 Apr. 25, 2024
See (22) Filed.
See (30) Foreign Application Priority Data.

(65) US 2024/0138229 A1 Apr. 25, 2024

(30) **Foreign Application Priority Data**

Oct. 20, 2022 (KR) 10-2022-0135361

Publication Classification

(51) **Int. Cl.**

H10K 59/60	(2006.01)
G06V 40/13	(2006.01)
H10K 59/38	(2006.01)
H10K 59/80	(2006.01)

(52) **U.S. Cl.**

CPC ***H10K 59/60*** (2023.02); ***G06V 40/1318*** (2022.01); ***H10K 59/38*** (2023.02); ***H10K 59/8791*** (2023.02)

(57) **ABSTRACT**

A display device including: a substrate; first to third light emitting portions on the substrate; a light sensing portion on the substrate and configured to sense an incident light, a light blocking layer having a light blocking opening that overlaps the light sensing portion; a first color filter on the first light emitting portion, and configured to transmit the first light, and block the second light and the third light; a second color filter on the second light emitting portion, overlapping the light blocking opening, and configured to transmit the second light, and block the first light and the third light; a third color filter on the third light emitting portion, and configured to transmit the third light, and block the first light and the second light; and a first light blocking pattern on the second color filter and overlapping a portion of the light blocking opening.