



US 20240237473A1

(19) **United States**

(12) **Patent Application Publication**  
**KANG et al.**

(10) **Pub. No.: US 2024/0237473 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY DEVICE AND METHOD OF  
MANUFACTURING DISPLAY DEVICE**

*H10K 59/121* (2006.01)

*H10K 59/38* (2006.01)

*H10K 59/80* (2006.01)

*H10K 71/20* (2006.01)

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si  
(KR)

(52) **U.S. Cl.**

CPC ..... *H10K 59/40* (2023.02); *H10K 59/1201*

(2023.02); *H10K 59/1213* (2023.02); *H10K*

*59/38* (2023.02); *H10K 59/879* (2023.02);

*H10K 71/233* (2023.02)

(72) Inventors: **Hyeo Ji KANG**, Yongin-si (KR); **Oh  
Jeong KWON**, Yongin-si (KR); **Tae  
Ho KIM**, Yongin-si (KR); **Seung Yeon  
JEONG**, Yongin-si (KR); **Mi Hwa  
LEE**, Yongin-si (KR); **Hong Yeon  
LEE**, Yongin-si (KR)

(57)

# **ABSTRACT**

(21) Appl. No.: **18/450,202**

(22) Filed: **Aug. 15, 2023**

(30) **Foreign Application Priority Data**

Jan. 10, 2023 (KR) ..... 10-2023-0003715

## **Publication Classification**

(51) **Int. Cl.**

*H10K 59/40* (2006.01)

*H10K 59/12* (2006.01)

A display device includes: a display part including a light emitting element on a base layer; and a sensor part on the display part and including a conductive pattern including an upper conductive pattern, and an inorganic layer covering the upper conductive pattern, wherein: the inorganic layer includes a first inorganic layer having a first refractive index and a second inorganic layer having a second refractive index less than the first refractive index, and the second inorganic layer is outside the first inorganic layer with respect to the base layer.

