



US 20240215116A1

(19) **United States**(12) **Patent Application Publication**
Matsui(10) **Pub. No.: US 2024/0215116 A1**(43) **Pub. Date: Jun. 27, 2024**(54) **HEATER AND PRODUCTION THEREOF**(71) Applicant: **Momentive Technologies Japan K.K.**,
Tokyo (JP)(72) Inventor: **Yoshihiko Matsui**, Sayo-cho (JP)(21) Appl. No.: **18/598,430**(22) Filed: **Mar. 7, 2024****Related U.S. Application Data**(63) Continuation of application No. 16/754,026, filed on
Apr. 6, 2020, filed as application No. PCT/JP2018/
036650 on Oct. 1, 2018.**Foreign Application Priority Data**

Oct. 30, 2017 (JP) 2017-209520

Publication Classification(51) **Int. Cl.**
H05B 3/06 (2006.01)
H01L 21/683 (2006.01)**H05B 3/10** (2006.01)**H05B 3/74** (2006.01)(52) **U.S. Cl.**CPC **H05B 3/06** (2013.01); **H01L 21/6833**
(2013.01); **H05B 3/10** (2013.01); **H05B 3/74**
(2013.01); **H05B 2203/002** (2013.01); **H05B**
2203/017 (2013.01)

(57)

ABSTRACT

Provided is a heater in which heater patterns are provided in parallel between terminals. Each terminal is divided into a divided terminal having electrical conduction only with one heater pattern, and a divided terminal having electrical conduction only with the other heater pattern. After a heater body is fabricated, in a state prior to mounting a feed bolt, resistance adjustment is performed with respect to each of a virtual series path formed between the divided terminals and a virtual series path formed between the divided terminals. Then the feed bolt is mounted to each divided terminal, whereby a plurality of virtual series heater patterns are placed in electrical conduction with each other, thus forming a parallel circuit.

