



US 20240244915A1

(19) **United States**

(12) **Patent Application Publication**
SHIN

(10) **Pub. No.: US 2024/0244915 A1**

(43) **Pub. Date: Jul. 18, 2024**

(54) **DISPLAY DEVICE**

(71) Applicant: **Samsung Display Co., LTD.**, Yongin-si (KR)

(72) Inventor: **HO-YONG SHIN**, Yongin-si (KR)

(21) Appl. No.: **18/377,061**

(22) Filed: **Oct. 5, 2023**

(30) **Foreign Application Priority Data**

Jan. 12, 2023 (KR) 10-2023-0004964

Publication Classification

(51) **Int. Cl.**

H10K 59/38	(2006.01)
H10K 59/122	(2006.01)
H10K 59/126	(2006.01)
H10K 59/35	(2006.01)
H10K 59/80	(2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/38** (2023.02); **H10K 59/122** (2023.02); **H10K 59/126** (2023.02); **H10K 59/352** (2023.02); **H10K 59/353** (2023.02); **H10K 59/877** (2023.02)

(57)

ABSTRACT

A display device includes: a substrate including a first pixel area and a second pixel area disposed adjacent to each other, each of the first pixel area and the second pixel area including a first light-emitting area, a second light-emitting area, a third light-emitting area, and a non-light-emitting area, a light-emitting element disposed in each of the first, second, and third light-emitting areas on the substrate, a bank layer disposed in the non-light-emitting area on the light-emitting element and defining first openings respectively overlapping the first light-emitting areas of the first and second pixel areas and a first central opening extending to the first openings, and a first color conversion layer including first quantum dots and filling the first openings and the first central opening.

